



# GLU- GONE

## CARPET GLUE REMOVER

**GLU-GONE IS A NON-FLAMMABLE, WATER BASED SOLVENT AND EMULSIFIER THAT SOFTENS AND BREAKS THE BOND OF MOST TYPES OF ADHESIVES, ALLOWING EASY REMOVAL. THE EMULSIFYING PROPERTY ALLOWS EASY WATER FLUSH OFF OF ANY RESIDUE.**

### PRODUCT HIGHLIGHTS

- **Nonflammable-Non-combustible:** Unlike most other glue removers, Glu-Gone is not only nonflammable, but it will not support combustion even when soaked into rags or mops. It is much safer to use.
- **No harsh or unpleasant odors:** Glu-Gone has a pleasant citrus-like odor.
- **Emulsifiable:** The Glu-Gone formula penetrates the mastic and softens it with emulsifying action so that after scraping off the bulk of the glue, the remainder can be easily washed off with water. A water wash will then leave the floor clean and ready to be re-coated with glue or any other treatment.
- **Fast and Easy:** Just spray, mop or brush Glu-Gone over the mastic deposits to be removed, and let it penetrate for 20 to 45 minutes depending on the thickness and type of mastic. When the layer is softened, just scrape it off, and rinse the floor. No further treatment is necessary.

Where the floor is to be stained, it is recommended that it be treated with Super Blue to remove any imbedded material in the pours of the concrete.

- **Available in 1 gallon and 5 gallon.**

### USES

Glu-Gone can be used on all types of floor substrates that have glue deposits, and where water can be used in the final rinse. It will not interfere with the adhesion of new glue or mastics, or the use of coatings or stains.

### QUICK LOOK:

**Type:** Emulsifiable glue and mastic remover

**Toxicity:** Harmful if swallowed

**VOC's:** ~160 mg/L

**Flammability:** Non-flammable

**Composition:** Water soluble citrus solvents and nonchlorinated solvents in a biodegradable surfactant solution

**Color:** Green

**Odor:** Pleasant

**Coverage:**

*\*Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,  
PLEASE SEE SDS.



\*Product warranty for one year from date of manufacture

Ground FX Flooring 11580 Route 37 Marion, IL 62959 P: (618) 988-6700 • F: (618) 551-8835 [www.groundfxflooring.com](http://www.groundfxflooring.com)



# GLU-GONE

## **HOW TO USE:**

1. Apply Glu-Gone full strength by spray or pour on and spread with a soft broom to thoroughly cover and penetrate the adhesive layer.
2. Allow the Glu-Gone to soak for 25-45 minutes or until adhesive is easily scraped up.
3. Scrape off adhesive and flush off any residue with water. Remove material according to local, state and federal regulations.

*Note: A small test area is recommended.*

## **PRECAUTIONARY STATEMENT:**

Avoid breathing dust/fumes/gas/mist/vapors/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash before reuse. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container according to local, state and federal regulations. Do not use, spill, or store in a way that will allow product or rinsate to enter streams, lakes or water ways where fish or marine life may be adversely affected. Use caution around plants and grass areas as this product could harm them.

## **FIRST AID:**

IF INGESTED: Drink two glasses of water. Do not induce vomiting. Get Immediate Medical Help.  
IF IN EYES: Flush thoroughly with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.  
IF ON SKIN: Rinse off thoroughly with soap and water. Wash contaminated clothing before reuse.  
EXCESSIVE INHALATION: Remove to fresh air. If breathing is difficult administer oxygen. Get Medical Help.

## **IN CASE OF FIRE:**

This product is non-flammable.

## **FOR PROFESSIONAL USE ONLY**

### **FOR EMERGENCY HELP**

24 Hours a Day contact:  
INFOTRAC at 1-800-535-5053

\*Product warranty for one year from date of manufacture

Ground FX Flooring 11580 Route 37 Marion, IL 62959 P: (618) 988-6700 • F: (618) 551-8835 [www.groundfxflooring.com](http://www.groundfxflooring.com)