



11580 Route 37
Marion, IL 62959
(618) 988-6700

17" HELL CAT

Severe Duty Floor Machine
w/360 Degree Internal Dust Pick Up

Stripping, Sanding, Resurfacing & Polishing



The HELL CAT is built for high productivity in the harshest jobs like concrete resurfacing, natural stone polishing, and wood screening and sanding. Designed with the powerful 1.5 HP 180 frame, TEFC AC motor fit with 11:1 hardened helical cut gears and an industrial grade steel coupler. This combination of motor and gears weighs 30 pounds more than a standard machine of similar size. Powered to drive sandpaper drivers, diamond pad drivers, Claw, Scraper and Orbitec tools.

The machine is built using a 16 gauge steel powder-coated brush cover with a 360 degree dust collecting duct and exhaust port connects to 1.5" and 2" vacuum hose. Remove the heaviest soils by adding the optional 50 lb. weight set with transport lock.

Power

- 1.5 HP, 180 frame, dual capacitor TEFC AC motor
- 115-230V, 60 Hz power (50 Hz optional)
- 50 ft., (12-3) 2-piece industrial power cord with twist lock
- Extra heavy-duty XHD steel helical-cut 11:1 gears with steel coupler

Engineered Design

- Proprietary brush cover with wraparound dust guard picks up dusts and debris
- Extra heavy-duty steel handle with vacuum hose support
- Heavy-duty motor guard protects the motor from impact damage
- Dual steel operating triggers with negative pressure on/off switch
- Thumb-operated safety switch. Comfortable vinyl-dipped foam grips
- 2" x 6" non-marking, load bearing ball bearing wheels
- Optional (2) 25 lb. removable weight set with locking pins and transport lock (#A360-17-2 -17"), (#A360-20-2 - 20")
- Optional Osprey Sprayer Kit (#TH-1010)

Safety Features:

- Quiet 66 dB operation. Meets GS42 standard.
- UL/CUL listed



Specifications

Model Item #	BRUTE 360-Black-17 F38-B (Black)
Model Item #	BRUTE 360-Chrome-17 F38-C (Chrome)
Machine Size	17 inch
Pad Size	16 inch
Pad Speed	165 RPM
Amp Draw	7.9 Amp
Weight	133 lbs.
All Sizes	
Motor	1.5 HP, 180 frame, TEFC dual capacitor AC
Power	115-230V, 60 Hz power (50 Hz optional)
Power Cord	50 ft., (12-3) 2-piece industrial w/ twist lock
Drive Gears	Triple-planetary XHD 11:1 helical-cut industrial
Sound Level (ave.)	66 dB - Meets GS42 standard



Handle is 3" Wider than Standard
The Handle-Mounted Hose Support Carries 1.5" and 2" Vacuum



Variable Handle Height Adjustment and Transport Lock



The Steel Brush Cover is Built with Ribbed Vacuum Port



360° Duct in the Brush Apron Directs Debris to the 2" Vacuum Port